


Chiodino *bollard*



Sizes



Light data and product code

Height (h)	Product Code	LED Power	LED CRI	LED Lumen	System Lumen	Beam Spread	Beam Angle	Beam Diameter	Beam Area	Beam Intensity
0.5 m	94 40 1X4	9,6W	>90	442 lm 2700K ^⓪ 470 lm 3000K ^⓪	412 cd/klm @3000K	283 lux 103 lux 38 lux 14 lux 5 lux	2 1 0 1 2	2 1 0 1 2	0,12 m ²	283 lux
1.0 m	94 40 2X4	9,6W	>90	442 lm 2700K ^⓪ 470 lm 3000K ^⓪	412 cd/klm @3000K	93 lux 45 lux 22 lux 10 lux 5 lux	2 1 0 1 2	2 1 0 1 2	0,24 m ²	93 lux
1.6 m	94 40 3X4	9,6W	>90	442 lm 2700K ^⓪ 470 lm 3000K ^⓪	412 cd/klm @3000K	44 lux 26 lux 15 lux 9 lux 5 lux	2 1 0 1 2	2 1 0 1 2	0,40 m ²	44 lux

Technical data

X = 9 → 602 lm 2700K^⓪
X = 1 → 640 lm 3000K^⓪

◇ 24V DC - dimmable PWM

IP65 | IK07

50 → cable 4,5 mts (2 x 0,5 mm²)
100 → cable 4 mts (2 x 0,5 mm²)
160 → cable 3,4 mts (2 x 0,5 mm²)

Power supply to be ordered separately
Alimentatore da ordinare separatamente

Technical notes

⓪ LED lumen - ⓪ System lumen

24V power supplies IP20

ON/OFF

89 56 104
□ 30W
165x38x23 mm
Supported
max product: 3

89 56 227
□ 100W
335x43x30 mm
Supported
max product: 10

DALI

89 56 222
□ 24W
196x38x25 mm
Supported
max product: 2

89 56 223
□ 75W
308x41x29 mm
Supported
max product: 7

24V power supplies IP67

ON/OFF

89 56 172
□ 40W
188x40x30 mm
Supported
max product: 4


89 56 221
□ 100W
230x52x33 mm
Supported
max product: 10

DALI

89 56 226
□ 24W
185x35x73 mm
Supported
max product: 2

89 56 021
□ 60W
190x53x35 mm
Supported
max product: 6

Accessories




89 45 036
Recessed box

Other power supplies available at page 338
Altri alimentatori disponibili a pag 338


Chiodino *spike*




Sizes




Light data and product code




50
94 02 1X4
9,6W LED CRI >90
442 lm 2700K ☉
470 lm 3000K ☉




412 cd/klm
@3000K




@3000K
h= 0.5 m
283 lux
103 lux
38 lux
14 lux
5 lux




100
94 02 2X4
9,6W LED CRI >90
442 lm 2700K ☉
470 lm 3000K ☉




412 cd/klm
@3000K




@3000K
h= 1.0 m
93 lux
45 lux
22 lux
10 lux
5 lux



160
94 02 3X4
9,6W LED CRI >90
442 lm 2700K ☉
470 lm 3000K ☉



412 cd/klm
@3000K



@3000K
h= 1.6 m
44 lux
26 lux
15 lux
9 lux
5 lux

Technical data

X = 9 → 602 lm 2700K ☉
X = 1 → 640 lm 3000K ☉

◇ 24V DC - dimmable PWM

IP65 | IK07

50 → cable 4,5 mts (2 x 0,5 mm²)
100 → cable 4 mts (2 x 0,5 mm²)
160 → cable 3,4 mts (2 x 0,5 mm²)

Power supply to be ordered separately
Alimentatore da ordinare separatamente

Technical notes

☉ LED lumen - ☉ System lumen

24V power supplies IP20

ON/OFF

89 56 104
☐ 30W
165x38x23 mm
Supported
max product: 3

89 56 227
☐ 100W
335x43x30 mm
Supported
max product: 10

DALI

89 56 222
☐ 24W
196x38x25 mm
Supported
max product: 2

89 56 223
☐ 75W
308x41x29 mm
Supported
max product: 7

24V power supplies IP67

ON/OFF

89 56 172
☐ 40W
188x40x30 mm
Supported
max product: 4

89 56 221
☐ 100W
230x52x33 mm
Supported
max product: 10

DALI

89 56 226
☐ 24W
185x35x73 mm
Supported
max product: 2

89 56 021
☐ 60W
190x53x35 mm
Supported
max product: 6

Other power supplies available at page 338
Altri alimentatori disponibili a pag 338